



## Allgemeine Informationen | *general information* und technische Eigenschaften | *and technical characteristics*

Eingangsspannung   <i>input voltage:</i>	12V DC
Material der Platine   <i>material of PCB:</i>	Aluminium   <i>aluminum</i>
Art der LED   <i>form of LED:</i>	SMD 3020
Abstrahlwinkel   <i>beam angle:</i>	120°
Abmessungen   <i>dimensions:</i>	600 x 4 x 3mm (Länge   <i>length:</i> max. 1800mm)
Brechpunktstand   <i>distance of the breakpoints:</i>	17,65mm - Löt pads an einer Seite   <i>solder pads at one side</i>
ESD Schutz   <i>ESD protection:</i>	1000V
Extras   <i>extra:</i>	3M Tape
Lebensdauer   <i>life time:</i>	Ts < 60°C - 50%/30.000h (Ts = Temperatur am Löt punkt   <i>temperature at soldering point</i> )

Artikelnummer <i>part number</i>	Anzahl der LED <i>quantity of LED</i>	Lichtfarbe <i>color temp.</i>	Strom <i>driving current</i>	Lichtstrom <i>luminous flux</i>	Leistungsaufn. <i>power cons.</i>
022Z-0600-34-001	102 LED/600mm (170LED/m)	3400K	18mA/LED	580lm	7,4W
022Z-0600-64-001	102 LED/600mm (170LED/m)	6400K	18mA/LED	580lm	7,4W